



It's nice to
look amazing
with so little
effort!

Tarkett ProGen™ and NuGen™ Cleaning, Care & Maintenance

A regular maintenance program should always be followed to preserve the factory finish and appearance of all luxury vinyl flooring. Refer to the complete Tarkett Maintenance instructions for more details.

Post-Installation

- Repeated exposure to direct sunlight may cause fading or discoloration. The use of drapes or blinds during peak sunlight hours is recommended.
- Both ProGen and NuGen Click are approved for installations in fully enclosed spaces that do not have permanent HVAC. In these areas, ensure that a minimum ½" expansion space is maintained around the entire perimeter against any fixed verticals. For areas with permanent HVAC, maintain temperatures between 55°-100°F (12.8°-37.8°C) and relative humidity between 40-70%.
- Often, furniture and appliances are equipped with feet that can scratch or damage Luxury Vinyl floors. Always use plywood panels to move these items across your flooring.

Routine Maintenance

- Make sure furniture and appliances are equipped with proper, non-staining glides or casters that have a minimum bearing surface in contact with the flooring of 1" square.
DO NOT use felt floor protectors.
- Dirt and debris that is tracked onto the floor can lead to scuffing, scratching, or dulling of the factory finish. Always use non-staining, latex-backed mats at entry ways.
- Sweeping or vacuuming (without a beater bar) can help to remove any tracked debris that is not caught by entry mats.
- Wipe up spills promptly and thoroughly with a damp cloth or mop.

Spot Treatment

- Scuffing can easily be removed with a white nylon pad dampened with a neutral cleaner.

- Most household spills can easily be cleaned with a damp cloth or mop and neutral cleaner. For tougher spots, a rag soaked in neutral cleaner may be placed over the spill for a short period to help remove any residue. For sticky spills, such as adhesive, gum, or grease, denatured alcohol applied to a clean white cloth may be used (Follow manufacturer's precautions when using denatured alcohol).
- Always remember to clean the area with a neutral cleaner after any spot treatment procedure.

Suggested Neutral Cleaners

Tarkett SureShine® Cleaner

- Dilute 4-6 oz in 1 gallon of water
- Apply with a damp mop. Do not saturate the floor.
- Allow the cleaner to dwell long enough to loosen soil from the floor. Rinse thoroughly to remove all soapy residue.

Ammonia

- Daily maintenance: Dilute ¼ cup of ammonia into 1 gallon of water
- Spot Treatment: Use at full strength
- Apply with a damp mop. Do not saturate the floor.

Optional Polish Application

Tarkett SureShine® Polish

- Available in both Matte Satin that will match the factory finish of the floor, as well as in Gloss to increase the shine.
- Apply as needed depending on frequency of foot traffic.
- Apply full strength and spread evenly with a microfiber-type mop.

Tarkett North America

30000 Aurora Road
Solon, OH 44139
USA: 1-877-TARKETT (1-877-827-5388)
Canada: 1-877-436-6267
www.tarkettna.com



Scan this code
to visit
Tarkett Home's
YouTube channel.

